

DATASHEET

JOHNSTONE'S PROFESSIONAL Exterior Timber Oil



Exterior Timber Oil

Extremely durable, fast drying, superior water based transparent oil for timber windows, doors, cladding, bi-folds, gates and more.



FEATURES AND BENEFITS

IDEAL SURFACE	New and weathered exterior hard & soft timber species, such as Western Red Cedar window and door joinery. Not suitable for decks
USES	Protecting vertical hardwood and softwood exterior timber cladding, windows, doors, bifolds, gates & pergolas
MOULD PROTECTION	Encapsulated biocide which is released slowly. Slow release means coating resists mould growth for up to 2 times longer versus conventional woodcare products
UV PROTECTION	Blocks out harmful UV rays for longer lasting results
WATER BASED FORMULA	Yes
AQUA PROTECT	Creates a highly durable barrier that repels water and resists mould, dirt and stains
GREATER TRANSPARENCY	Designed for greater transparency to allow the timber grain to be more visible
EASE OF APPLICATION	The application properties of Johnstone's make it easy to apply to all timber substrates
AUSTRALIAN MADE	Yes

PRODUCT SPECIFICATIONS

FINISH	Semi-transparent, low lustre
CLEAN UP	Water
VOC LEVEL	48.1g per litre
DRY TIMES: TOUCH DRY	30 minutes (Note: All timings quoted at 25°C and 50% humidity. Cooler or humid conditions may require longer.)
DRY TIMES: RECOAT	1 hour (Note: All timings quoted at 25°C and 50% humidity. Cooler or humid conditions may require longer.)
DRY FILM THICKNESS	18 Microns at 12m ² spread rate
RECOMMENDED COATS	3
COVERAGE	Up to 12m ² per litre (Subject to timber porosity, species and condition)

DATASHEET

PACK SIZES	1L, 4L, 10L
COLOUR RANGE	Natural, Merbau, Jarrah, Walnut, Teak

SURFACE PREPARATION

NEW HARDWOOD TIMBER	Allow the timber to naturally weather for 6 weeks. During this period, wet timber with a garden hose as regularly as possible. This will flush the natural timber tannins from the timber substrate and reduce the risk of timber tannin residue appearing once exterior oil has been applied. Alternatively, apply Johnstone's Professional Tannin & Oil Remover followed by Johnstone's Professional Deck & Timber Cleaner following label instructions. Allow to completely dry. Lightly sand timber surface. This will raise the fibres of the timber grain and provide a greater key for the Johnstone's Professional Timber Oil to adhere to
SOFTWOODS (INCLUDING TREATED PINE AND WESTERN RED CEDAR)	Ensure timber surface is dry, clean and free from dirt and debris prior to application
PREVIOUSLY PAINTED OR VARNISHED TIMBER	Remove previously coated material back to bare timber using Johnstone's Professional Timber Stripper, or by sanding. Clean timber with Johnstone's Professional Deck & Timber Cleaner following label instructions to remove any contaminants such as mould or tannin bleed residue. Allow to completely dry prior to coating
PREVIOUSLY STAINED AND OILED TIMBER	Clean timber with Johnstone's Professional Deck & Timber Cleaner, rinse off timber substrate following label instructions and allow to completely dry. Lightly sand the timber surface to improve adhesion. Ensure timber is free from dirt, dust and contaminants prior to the application of Johnstone's Professional Timber Oil
WEATHERED AND GREY TIMBER	For best results, clean timber with Johnstone's Professional Deck & Timber Cleaner following label instructions. Use a high pressure washer to remove residue and allow to completely dry. Additional light sand may be required to remove any grey areas not removed by Johnstone's Professional Deck & Timber Cleaner. Ensure surface is dirt and dust free prior to the application of Johnstone's Professional Timber Oil

APPLICATION

STIRRING	Stir thoroughly with a broad flat paddle before and during use
EQUIPMENT	Brush, Deck Brush, Lambs Wool Applicator Pad
APPLICATION METHODS	Apply liberally along the length of the timber boards including exposed edges and end grain preferably by brush or applicator pad. Initially applied, the Johnstone's Professional Timber Oil will look slightly opaque however, will dry to a semi-transparent finish allowing the timber grain to remain visible. Apply two coats allowing 1 hour between the first and second coat. For increased durability and longevity, a third coat is recommended
MAINTENANCE	Re-apply as the timber changes colour and presents a dull appearance or when water repellency diminishes due to weathering. Follow surface preparation instructions prior to applying a maintenance coat of Johnstone's Professional Timber Oil
IMPORTANT APPLICATION INFORMATION	Do not apply this product in temperatures below 10°C or above 35°C or when heavy rain or dew is expected during the drying period. In hot temperatures, do not apply in direct sunlight. Attempt to coat when project is shaded

DATASHEET

PRECAUTIONS

STORAGE INFORMATION	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area. Do not store below 5°C temperature. Keep containers sealed when not in use
SAFETY AND FIRST AID	<p>KEEP OUT OF REACH OF CHILDREN Avoid skin and eye contact. Provide adequate ventilation. If using inside, keep windows and doors open during application and drying time</p> <p>IF SWALLOWED: Give plenty of water to drink. Seek medical advice EYE CONTACT: Rinse with plenty of running water. Seek medical advice if irritation occurs</p> <p>24 HOUR MEDICAL EMERGENCY RESPONSE SERVICE CALL: AUSTRALIA: 1800 883 254 NEW ZEALAND: 0800 000 096</p>
ENVIRONMENTAL INFO	Do not pour left over content down the drain. Unwanted material should be brushed out on newspaper allowed to dry then disposed of via domestic waste collections. Empty paint containers should be left open in a well ventilated area to dry out. When dry, recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first

DISCLAIMER

*12 MONTH AQUA PROTECT GUARANTEE: Johnstone's Professional decking and exterior range (excluding Interior / Exterior Clear) is guaranteed against peeling, flaking and blistering for 12 months if used in accordance with printed directions on pack and applied to suitable and properly prepared surfaces. If this guarantee is not met, we will replace the product or refund your money. This guarantee is given by PPG Industries Australia Pty Limited and applies to defects in the manufacture or formulation of the product. This guarantee does not cover peeling, flaking and blistering caused by failure of previously applied products, contaminated substrates, unsound problems caused by environmental or underlying structural issues, or product failure caused by other factors beyond our control. We are not liable for the cost of labour or any other direct or indirect loss or damage arising from a breach of this guarantee. Customers are responsible for all costs of claiming under this guarantee. To claim, customers must write to us or call our Customer Service number to request a claim form. The benefits provided by this guarantee are in addition to other rights and remedies under the law. If you are a consumer within the meaning of the Australian or New Zealand Consumer Law: Our goods come with guarantees that cannot be excluded under the Australian Consumer Law and Consumer Guarantees Act, respectively. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. For terms and conditions visit www.johnstoneswoodcare.com.au

Any information provided by PPG Industries Australia Pty Ltd and its related entities relating to PPG products or their use and application (for example, information contained in a PPG paint system, Specification, or Data Sheet) is accurate and reliable at the time of publication. However, such information is general in nature. You must ensure that the information is current and suitable for the specific conditions for your project. If you need technical information for your circumstances, you should contact Customer Service Australia on 131 686 or info@johnstoneswoodcare.com.au.

PPG Industries Australia Pty Ltd and its related entities are not liable for any loss (including indirect, special or consequential loss, or loss of profits), expense, or damage suffered in connection with (a) such information, or (b) any information provided by a third party (including where that information is provided on a PPG website). Nothing in this disclaimer restricts, excludes or modifies or purports to restrict, exclude or modify any statutory rights under any applicable law including the Competition and Consumer Act 2010 (Cth) or the operation of any express guarantee.

CUSTOMER SERVICE/COMPANY CONTACT

Customer Service Australia: 131 686 Further information: www.johnstoneswoodcare.com.au Email: info@johnstoneswoodcare.com.au